

FLYAWAY

Mobile-Uplink Systems (1.2m C-Band)



Features

- Excellent Value – Better Value and Lower Operating Costs Than Any Competing Uplink Systems
- Portable – Air Craft Baggage Shippable
- Fast Response – Dependable, Reliable Alignment, Set Up and Operation
- Rugged – Designed For Harsh Environments
- Fast Deployment – Can Be Installed by Only One Person
- Easy Operation – Easy Front Access to All the System's Input's, Outputs and Monitoring Ports
- Universal System – System Accommodates World Voltages and Color Standards
- Reliability – Our Systems are 100% Field Tested

Applications

News Agencies, Universities, Corporations, Religious Institutions, Any Entity that Needs Fast and Temporary Satellite Access

Excellent Value, Rugged, Reliable Uplink System

ATCi introduces FlyAway Mobile-Uplink System, a totally new, cost-effective concept in C & Ku-Band portable systems for quick, dependable satellite communication response. The ATCi FlyAway Mobile-Uplink System is a complete C or Ku-Band portable satellite terminal system capable of uplinking any video content over satellite.

Complete FlyAway mobile-Uplink System includes: C or Ku TX/RX antenna, SSPA, Upconverter, modulator, encoder, multiplexer, IRD, access panel, complete integration and Spectrum Analyzer test unit. All for a very economical price.

FlyAway Mobile-Uplink System Takes Lightweight and Convenience to a Whole New Level

The portable system consists of 4 boxes, 3 of which hold the antenna (see picture) and the fourth box houses the electronic equipment. In addition to its superior performance, the antenna system is lightweight with minimum parts for fast deployment. The system's electronics is housed in a rugged portable rack with shock mounts and wheels (removable) for protection and ease of movement both onsite and offsite. Just hookup your video and audio source to the front panel, direct your antenna and start broadcasting!

Specifications: FlyAway Mobile Uplink Systems (1.2m C-Band)

Antenna:

Size: 1.2m
Band: C band (5.85 - 6.425 GHz TX, 3.4 - 4.2 GHz Rx)
Gain: 39.8 dBi
Feed interface: WR137 or N-type coax
Noise Temperature: 50 K @ 10 degrees elevation
Transmit cross polarization: 30 dB

RF and Encoding system (electronics in rack):

Frequency range: 5.85 - 6.425 GHz
RF power output: 150 - 200 Watts
Modulation scheme: QPSK
Maximum data rate: 17.5 Mbps
FEC: 1/2, 3/4, 5/6, 7/8
Video Format: NTSC, PAL
Video input: Analog composite or Digital SDI
Closed caption: Supported

Monitoring system:

The following test points are available:

- 1) LNB output
- 2) Modulator: L band output
- 3) Transmitter: C band output @ 40 dB attenuation
- 4) IRD: Analog and ASI output